



### Specifications

ACT® Registered Certification Marks



|                  |                                |
|------------------|--------------------------------|
| Application      | Upholstery, Indoor             |
| Content          | 100% Biodegradable Vinyl       |
| Backing          | 100% Biodegradable Polyester   |
| Finish / Topcoat | Soil & Stain Resistant Topcoat |
| Weight           | 31.0 oz./yd.                   |
| Width            | 54.000"                        |
| Fabric Shown     | Up the Roll                    |
| Origin           | Taiwan                         |

### Product Attributes

- Antibacterial
- Sulfide Stain Resistant

### Performance Characteristics

|  |                                 |
|--|---------------------------------|
| Abrasion Resistance<br>ASTM D4157                | 250,000 Double Rubs             |
| Flex Resistance<br>ASTM D 2097                   | 25,000 Cycles                   |
| Break Strength<br>ASTM D751-06                   | Warp: 95.8 lbs / Weft: 82.2 lbs |
| Tear Strength, Tongue Tear<br>ASTM D751-06       | Warp: 10.5 lbs / Weft: 13.7 lbs |
| Tear Strength, Tack/Trap Tear<br>ASTM D751-06    | Warp: 47.9 lbs / Weft: 46.1 lbs |
| Wet Crocking<br>AATCC 8                          | Grade: 5                        |
| Dry Crocking<br>AATCC 8                          | Grade: 5                        |
| Colorfastness to Light<br>AATCC 16 (Hours/Grade) | Hours: 300 / Grade: 4           |
| Adhesion of Coating<br>ASTM D751                 | Warp: 4.16 lbs / Weft: 3.86 lbs |
| Cold Crack<br>CFFA 10                            | - 20 F                          |

### Flammability

- FMVSS 302
- CA Technical Bulletin 117-2013
- UFAC Class 1
- NFPA 260

### Environment/Certifications

- California AB-2998 Compliant
- Formaldehyde Free
- REACH Compliant
- Healthier Hospitals Compliant
- Will biodegrade >90% in landfill
- PFAS Free
- Phthalate Free
- RoHS Compliant
- Prop 65 Compliant
- No detectable chemicals of concern in

environment within 2 Years per ASTM D5511 post-degradation soil

- No negative effect on post-degradation soil per ASTM E1963
- Low VOC



(800) 347-8344

[UNITEDFABRICS.COM](http://UNITEDFABRICS.COM)

[SALES@UNITEDFABRICS.COM](mailto:SALES@UNITEDFABRICS.COM)