



Specifications

ACT® Registered Certification Marks



| | |
|------------------|--------------------------------|
| Application | Upholstery, Indoor |
| Content | 100% Biodegradable Vinyl |
| Backing | 100% Biodegradable Polyester |
| Finish / Topcoat | Soil & Stain Resistant Topcoat |
| Weight | 31.0 oz./yd. |
| Width | 54.000" |
| Fabric Shown | Up the Roll |
| Origin | Taiwan |

Product Attributes

- Antibacterial
- Sulfide Stain Resistant

Performance Characteristics

| | |
|--|---------------------------------|
| Abrasion Resistance ASTM D4157 | 250,000 Double Rubs |
| Flex Resistance ASTM D 2097 | 25,000 Cycles |
| Break Strength ASTM D751-06 | Warp: 95.8 lbs / Weft: 82.2 lbs |
| Tear Strength, Tongue Tear ASTM D751-06 | Warp: 10.5 lbs / Weft: 13.7 lbs |
| Tear Strength, Tack/Trap Tear ASTM D751-06 | Warp: 47.9 lbs / Weft: 46.1 lbs |
| Wet Crocking AATCC 8 | Grade: 5 |
| Dry Crocking AATCC 8 | Grade: 5 |
| Colorfastness to Light AATCC 16 (Hours/Grade) | Hours: 300 / Grade: 4 |
| Adhesion of Coating ASTM D751 | Warp: 4.16 lbs / Weft: 3.86 lbs |
| Cold Crack CFFA 10 | - 20 F |

Flammability

- FMVSS 302
- CA Technical Bulletin 117-2013
- UFAC Class 1
- NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- Formaldehyde Free
- REACH Compliant
- Healthier Hospitals Compliant
- Will biodegrade >90% in landfill
- PFAS Free
- Phthalate Free
- RoHS Compliant
- Prop 65 Compliant
- No detectable chemicals of concern in

environment within 2 Years per ASTM D5511 post-degradation soil

- No negative effect on post-degradation soil per ASTM E1963
- Low VOC



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM