



NAUGAHYDE®

Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl
Backing	100% Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	27.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	USA

Product Attributes

- Oil Resistant
- Sulfide Stain Resistant

Product Notes

- Inventory in Transition to California AB-2998 Compliance

Performance Characteristics

Abrasion Resistance ASTM D4157	1,500,000 Double Rubs
Flex Resistance ASTM D2097	15,000 Cycles
Break Strength ASTM D751-06	Warp: 55 lbs / Weft: 55 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 12 lbs / Weft: 10 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4
Adhesion of Coating ASTM D751	Warp: 3 lbs / Weft: 3 lbs
Cold Crack CFFA 10	- 20 F

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013

Environment/Certifications

- PFAS Free
- RoHS Compliant
- REACH Compliant

