



OUTDOOR



BLEACH
CLEANABLE

Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor/Outdoor
Content	100% PVC Vinyl
Backing	Polyester Knit
Finish / Topcoat	Resilience TX Soil/Stain Protection
Weight	30.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	China
Collection	Atlas

Product Notes

- Prop 65 Compliant
- Inventory in Transition to California AB-2998 Compliance

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Break Strength ASTM D751-06	Warp: 95 lbs / Weft: 73 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 11.9 lbs / Weft: 15.4 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 67 lbs / Weft: 43 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Cold Crack -20 Degrees	

Flammability

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260