



Specifications

ACT® Registered Certification Marks     

Application	Upholstery, Indoor
Content	100% Polyurethane (PU)
Backing	100% Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat with Ink Resistant Technology
Weight	20.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	China
Collection	Writer's Block (2017 Fandeck) Writer's Block 2 (2020 Fandeck)

Product Attributes

- Antibacterial
- Mildew Resistant
- Sulfide Stain Resistant

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Hydrolysis Resistance ISO 1419 (Tropical Test Method C)	7 weeks
Break Strength ASTM D751-06	Warp: 144 lbs / Weft: 113 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 4.4 lbs / Weft: 8.5 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 57.3 lbs / Weft: 42.9 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 11.4 lbs / Weft: 10.8 lbs
Cold Crack CFFA 10	- 20 F

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
- Formaldehyde Free
- Phthalate Free
- PFAS Free



- REACH Compliant
- Healthier Hospitals Compliant

- RoHS Compliant
- Prop 65 Compliant