



Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% Polyurethane
Backing	Polyester Knit
Finish / Topcoat	Writer's Block Stain Resistance
Weight	20.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	China
Collection	Writer's Block Fandeck

Product Attributes

- Ink Resistant
- PVC Free

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Hydrolysis Resistance ISO 1419 (Tropical Test Method C)	7 weeks
Break Strength ASTM D751-06	Warp: 144 lbs / Weft: 113 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 4.4 lbs / Weft: 8.5 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 57.3 lbs / Weft: 42.9 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 11.4 lbs / Weft: 10.8 lbs
Cold Crack -20 Degrees	

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013