




Specifications

Table with 2 columns: Specification Name and Value. Rows include ACT® Registered Certification Marks, Application (Upholstery, Indoor), Content (95% Polyurethane (PU), 5% Silicone), Backing (100% Polyester), Finish / Topcoat (Soil & Stain Resistant Topcoat with Ink Resistant Technology), Weight (19.0 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), Origin (Taiwan), and Collection (Writer's Block 2 (2020 Fandek)).

Product Attributes

- Antibacterial
Mildew Resistant
Sulfide Stain Resistant

Performance Characteristics

Table with 2 columns: Performance Characteristic and Value. Rows include Abrasion Resistance (250,000 Double Rubs), Hydrolysis Resistance (15 weeks), Break Strength (Warp: 118 lbs / Weft: 96 lbs), Tear Strength, Tongue Tear (Warp: 10.4 lbs / Weft: 12.1 lbs), Tear Strength, Tack/Trap Tear (Warp: 69.5 lbs / Weft: 62.4 lbs), Wet Crocking (Grade: 5), Dry Crocking (Grade: 5), Colorfastness to Light (Hours: 200 / Grade: 4), Adhesion of Coating (Warp: Full Bond / Weft: Full Bond), and Cold Crack (- 20 F).

Flammability

- UFAC Class 1
NFA 260
CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
Phthalate Free
Formaldehyde Free



- REACH Compliant
- Healthier Hospitals Compliant

- RoHS Compliant
- Prop 65 Compliant