



Specifications

ACT® Registered Certification Marks



| | |
|--------------|--------------------|
| Application | Upholstery, Indoor |
| Content | 100% PVC |
| Backing | 100% Polyester |
| Weight | 31.4 oz./yd. |
| Width | 54.000" |
| Fabric Shown | Up the Roll |
| Origin | Taiwan |
| Collection | Club |

Product Attributes

- Ink Resistant

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant

Performance Characteristics

| | |
|--|---------------------------------|
| Abrasion Resistance ASTM D4157 | 100,000 Double Rubs |
| Break Strength ASTM D751-06 | Warp: 105 lbs / Weft: 92 lbs |
| Tear Strength, Tongue Tear ASTM D751-06 | Warp: 6.4 lbs / Weft: 7.5 lbs |
| Tear Strength, Tack/Trap Tear ASTM D751-06 | Warp: 54.3 lbs / Weft: 42.9 lbs |
| Wet Crocking AATCC 8 | Grade: 4 |
| Dry Crocking AATCC 8 | Grade: 4 |
| Colorfastness to Light AATCC 16 (Hours/Grade) | Hours: 300 / Grade: 4 |
| Adhesion of Coating ASTM D751 | Warp: 6.3 lbs / Weft: 6.3 lbs |
| Cold Crack -20 Degrees | |

Flammability

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260