



**Specifications**

ACT® Registered Certification Marks     

Application	Upholstery, Indoor
Content	100% PVC
Backing	100% Polyester
Weight	31.4 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan
Collection	Club

**Product Attributes**

- Ink Resistant

**Product Notes**

- Prop 65 Compliant
- California AB-2998 Compliant

**Performance Characteristics**

Abrasion Resistance ASTM D4157	100,000 Double Rubs
Break Strength ASTM D751-06	Warp: 105 lbs / Weft: 92 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 6.4 lbs / Weft: 7.5 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 54.3 lbs / Weft: 42.9 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 300 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 6.3 lbs / Weft: 6.3 lbs
Cold Crack -20 Degrees	

**Flammability**

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260