



OUTDOOR



BLEACH
CLEANABLE



ANTIMICROBIAL

Boltaflex®

Specifications

ACT® Registered Certification Marks     

Application	Upholstery, Indoor/Outdoor
Content	100% PVC Vinyl
Backing	100% Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	36.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Thailand

Product Attributes

- Antibacterial
 - Sulfide Stain Resistant
- Oil Resistant

Performance Characteristics

Abrasion Resistance ASTM D4157	1,300,000 Double Rubs
Flex Resistance ASTM D2097	25,000 Cycles
Break Strength ASTM D5034	Warp: 110 lbs / Weft: 85 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 25 lbs / Weft: 25 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light CFFA 2 (Hours/Grade)	Hours: 650 / Class: 4
Adhesion of Coating ASTM D751	Warp: 3 lbs / Weft: 3 lbs
Cold Crack CFFA 10	- 20 F

Flammability

- UFAC Class 1
 - CA Technical Bulletin 117-2013
 - IMO
- BIFMA Class 1
 - NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- PFAS Free