



PERMANENT SOIL & STAIN

Specifications

ACT® Registered Certification Marks 

|                  |                                   |
|------------------|-----------------------------------|
| Application      | Upholstery, Indoor                |
| Content          | 100% Polyester                    |
| Backing          | 100% Polyester                    |
| Finish / Topcoat | Permanent Soil & Stain Protection |
| Weight           | 14.2 oz./yd.                      |
| Width            | 54.000"                           |
| Fabric Shown     | Up the Roll                       |
| Origin           | China                             |
| Collection       | <a href="#">525: Explorer</a>     |

Performance Characteristics

|                                                  |                                 |
|--------------------------------------------------|---------------------------------|
| Abrasion Resistance<br>ASTM D4157                | 90,000 Double Rubs*             |
| Pilling<br>ASTM D3511                            | Class 5                         |
| Seam Slippage<br>ASTM D4034                      | Warp: 41 lbs / Weft: 47.6 lbs   |
| Break Strength<br>ASTM D5034                     | Warp: 94.4 lbs / Weft: 86.4 lbs |
| Wet Crocking<br>AATCC 8                          | Grade: 5                        |
| Dry Crocking<br>AATCC 8                          | Grade: 5                        |
| Colorfastness to Light<br>AATCC 16 (Hours/Grade) | Hours: 40 / Grade: 4            |

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Flammability

-  NFPA  
Technical  
Bulletin  
117-  
2013

Environment/Certifications

- California AB-2998 Compliant
- PFAS Free
- Prop 65 Compliant