




Specifications

Table with 2 columns: Specification, Value. Rows include ACT® Registered Certification Marks, Application (Upholstery, Indoor), Content (100% PVC Vinyl), Backing (100% Polyester), Finish / Topcoat (Soil & Stain Resistant Topcoat), Weight (26.0 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), Origin (Colombia), and Collection (726: Comfort Vinyls).

Product Attributes

- Anti-Static
- Sulfide Stain Resistant

Performance Characteristics

Table with 2 columns: Performance Characteristic, Value. Rows include Abrasion Resistance (100,000 Double Rubs), Flex Resistance (30,000 Cycles), Tear Strength, Tongue Tear (Warp: 8.7 lbs / Weft: 9.8 lbs), Wet Crocking (Grade: 4), Dry Crocking (Grade: 4), Colorfastness to Light (Hours: 1,000 / Grade: 4), Adhesion of Coating (Warp: 3.3 lbs / Weft: 3.3 lbs), and Cold Crack (10 F).

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
- Prop 65 Compliant
- PFAS Free
- RoHS Compliant

