



### Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	95% Polyurethane (Polycarbonate) 5% Silicone
Backing	100% Polyester
Finish / Topcoat	Writer's Block Stain Resistance
Weight	19.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan
Collection	Writers Block Fandeck 2

### Product Attributes

- Ink Resistant
- PVC Free

### Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant

### Performance Characteristics

Abrasion Resistance ASTM D4157	300,000 Double Rubs
Hydrolysis Resistance ISO 1419 (Tropical Test Method C)	15 weeks
Break Strength ASTM D751-06	Warp: 182 lbs / Weft: 126 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 11 lbs / Weft: 15 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 67.1 lbs / Weft: 65.3 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751 (Full Bond)	Warp: Full Bond / Weft: Full Bond
Cold Crack -20 Degrees	

### Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013