



UNITED FABRICS  
EXCLUSIVE



STAIN  
RESISTANT

PERMANENT SOIL & STAIN

### Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% Polyester
Backing	Acrylic
Finish / Topcoat	Permanent Soil & Stain Protection
Weight	17.3 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Turkey
Repeat Horizontal	.250"
Repeat Vertical	1.200"

### Performance Characteristics

Abrasion Resistance ASTM D4157	60,000 Double Rubs
Pilling ASTM D3511	Class 5
Seam Slippage ASTM D4034	Warp: 77 lbs / Weft: 65 lbs
Break Strength ASTM D5034	Warp: 310 lbs / Weft: 191 lbs
Wet Crocking AATCC 8	Grade: 4.5
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 40 / Grade: 4.5

### Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013

### Environment/Certifications

- California AB-2998 Compliant
- PFAS Free



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM