



Specifications

Table with 2 columns: Specification Name and Value. Rows include ACT® Registered Certification Marks, Application (Upholstery, Indoor), Content (100% Polyurethane (PU)), Backing (100% Polyester), Finish / Topcoat (Soil & Stain Resistant Topcoat with Ink Resistant Technology), Weight (20.0 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), Origin (China), and Collection (Writer's Block (2017 Fandek)).

Product Attributes

- Antibacterial
Mildew Resistant
Sulfide Stain Resistant

Performance Characteristics

Table with 2 columns: Performance Characteristic and Value. Rows include Abrasion Resistance (250,000 Double Rubs), Hydrolysis Resistance (7 weeks), Seam Slippage (Warp: 57.3 lbs / Weft: 42.9 lbs), Tear Strength (Warp: 4.4 lbs / Weft: 8.5 lbs), Tear Strength, Tack/Trap Tear (Warp: 57.3 lbs / Weft: 42.9 lbs), Wet Crocking (Grade: 5), Dry Crocking (Grade: 5), Colorfastness to Light (Hours: 200 / Class: 4.5), Adhesion of Coating (Warp: 11.4 lbs / Weft 10.8 lbs), and Cold Crack (- 20 F).

Flammability

- UFAC Class 1
NFPA 260
CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
Phthalate Free
Formaldehyde Free



- REACH Compliant
- Healthier Hospitals Compliant

- RoHS Compliant
- Prop 65 Compliant