

HINGE

16 Boulder

UNITED
SINCE *Fabrics* 1946



UNITED FABRICS
EXCLUSIVE



STAIN
RESISTANT



MADE IN
THE USA

PERMANENT SOIL & STAIN

Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	93% Olefin 7% Polyester
Backing	Acrylic
Finish / Topcoat	Permanent Soil/Stain Protection
Weight	20.2 oz./yd.
Width	54.000"
Fabric Shown	Railroaded
Origin	USA
Repeat Horizontal	5.000"
Repeat Vertical	5.625"
Collection	Color Trends Newsprint Naturals

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant
- PFAS Free

Performance Characteristics

Abrasion Resistance ASTM D4157	50,000 Double Rubs
Pilling ASTM D3511 (Brush Test)	Class 3
Seam Slippage ASTM D4034 (Grab Test)	Warp: 83 lbs / Weft: 93 lbs
Break Strength ASTM D5034	Warp: 250 lbs / Weft: 305 lbs
Wet Crocking AATCC 8	Grade: 3
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 40 / Grade: 4

Flammability

- CA Technical Bulletin 117-2013



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM