



Specifications

Table with 2 columns: Specification Name and Value. Rows include ACT® Registered Certification Marks, Application (Upholstery, Indoor), Content (100% Polyurethane (PU)), Backing (100% Polyester), Finish / Topcoat (Soil & Stain Resistant Topcoat with Ink Resistant Technology), Weight (25.4 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), and Origin (China).

Product Attributes

- Sulfide Stain Resistant

Performance Characteristics

Table with 2 columns: Performance Characteristic and Value. Rows include Abrasion Resistance (250,000 Double Rubs), Hydrolysis Resistance (10 weeks), Tear Strength (Warp: 8.9 lbs / Weft: 12 lbs), Tear Strength, Tack/Trap Tear (Warp: 83.9 lbs / Weft: 83 lbs), Wet Crocking (Grade: 5), Dry Crocking (Grade: 5), Colorfastness to Light (Hours: 200 / Class: 4.5), Adhesion of Coating (Warp: 4.42 lbs / Weft 4.48 lbs), and Cold Crack (- 20 F).

Flammability

- UFAC Class 1, NFPA 260, CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant, PFAS Free, Formaldehyde Free, Phthalate Free, REACH Compliant, Healthier Hospitals Compliant, Prop 65 Compliant, RoHS Compliant



