



Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl
Backing	100% Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	5.7 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Colombia
Collection	Comfort Vinyls

Product Attributes

- Anti-Static
- Sulfide Stain Resistant

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 Double Rubs
Flex Resistance ASTM D2097	30,000 Cycles
Tear Strength, Tongue Tear ASTM D2261	Warp: 5.6 lbs / Weft: 5.9 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 1,000 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 3.3 lbs / Weft: 3.3 lbs
Cold Crack CFFA 10	- 10 F

Flammability

- UFAC Class 1
 - NFPA 260
- CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
 - Phthalate Free
- PFAS Free