



## Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% Biodegradable Vinyl
Backing	100% Biodegradable Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	31.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan

## Product Attributes

- Antibacterial
- Sulfide Stain Resistant

## Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Flex Resistance ASTM D 2097	25,000 Cycles
Break Strength ASTM D751-06	Warp: 88.5 lbs / Weft: 71.5 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 9.6 lbs / Weft: 12.6 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 46.8 lbs / Weft: 45.4 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 300 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 4.11 lbs / Weft: 5.03 lbs
Cold Crack CFFA 10	- 20 F

## Flammability

- FMVSS 302
- CA Technical Bulletin 117-2013
- UFAC Class 1
- NFPA 260

## Environment/Certifications

- California AB-2998 Compliant
- Formaldehyde Free
- REACH Compliant
- Healthier Hospitals Compliant
- Will biodegrade >90% in landfill
- PFAS Free
- Phthalate Free
- RoHS Compliant
- Prop 65 Compliant
- No detectable chemicals of concern in

environment within 2 Years per ASTM D5511 post-degradation soil

- No negative effect on post-degradation soil per ASTM E1963
- Low VOC



(800) 347-8344

[UNITEDFABRICS.COM](http://UNITEDFABRICS.COM)

[SALES@UNITEDFABRICS.COM](mailto:SALES@UNITEDFABRICS.COM)