



STAIN
RESISTANT



MOISTURE
BARRIER



BLEACH
CLEANABLE



ANTIMICROBIAL

Specifications

ACT® Registered Certification Marks 

Application	Upholstery, Indoor
Content	94% Polyester 4% Polyurethane 2% Silicone
Backing	Polyurethane
Finish / Topcoat	Supreen Soil & Stain Protection with Liquid Barrier
Weight	21.5 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	China
Collection	520: Supreen Textures

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 Double Rubs*
Pilling ASTM D3511 (Brush Test)	Class 5
Seam Slippage ASTM D4034 (Grab Test)	Warp: 82.5 lbs / Weft: 80 lbs
Break Strength ASTM D5034	Warp: 302 lbs / Weft: 80 lbs
Wet Crocking AATCC 8	Grade: 4.5
Dry Crocking AATCC 8	Grade: 4.5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 40 / Grade: 4.5

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

Flammability

-  ACCA
Class Technical
1 Bulletin
117-
2013
- NFPA
260

Environment/Certifications

- California AB-2998 Compliant
 - Prop 65 Compliant
- PFAS Free
- UNITEDFABRICS.COM
- SALES@UNITEDFABRICS.COM