




Specifications

ACT® Registered Certification Marks     

Application	Upholstery, Indoor
Content	100% PVC
Backing	Polyester
Finish / Topcoat	Resilience TX Soil/Stain Protection
Weight	30.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan
Collection	Vinyl Binder

Product Notes

- Prop 65 Compliant
- Inventory in Transition to California AB-2998 Compliance

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Break Strength ASTM D751-06	Warp: 121 lbs / Weft: 125 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 9.8 lbs / Weft: 11.7 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 44.8 lbs / Weft: 53.7 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 4.3 lbs / Weft: 4.6 lbs
Cold Crack -20 Degrees	

Flammability

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260