


PASCAL

61 Minty

UNITED
SINCE *Fabrics* 1946



STAIN
RESISTANT



MOISTURE
BARRIER



BLEACH
CLEANABLE



ANTIMICROBIAL/
ANTIBACTERIAL

Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	89% Polyester 9% Polyurethane 2% Silicone
Backing	Polyurethane
Finish / Topcoat	Supreen Liquid Barrier
Weight	14.6 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	China
Collection	Supreen Textures

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant
- PFAS Free

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 Double Rubs
Pilling ASTM D3511 (Brush Test)	Class 5
Seam Slippage ASTM D4034 (Grab Test)	Warp: 94 lbs / Weft: 83.5 lbs
Break Strength ASTM D5034	Warp: 249 lbs / Weft: 79 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 40 / Grade: 4.5

Flammability

- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM