



**STAIN
RESISTANT**



**MOISTURE
BARRIER**



**BLEACH
CLEANABLE**



**ANTIMICROBIAL/
ANTIBACTERIAL**

Specifications

ACT® Registered Certification Marks



| | |
|------------------|-------------------------------------------------|
| Application | Upholstery, Indoor |
| Content | 89% Polyester 9% Polyurethane 2% Silicone |
| Backing | Polyurethane |
| Finish / Topcoat | Supreen Liquid Barrier |
| Weight | 14.6 oz./yd. |
| Width | 54.000" |
| Fabric Shown | Up the Roll |
| Origin | China |
| Collection | Supreen Textures |

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant
- PFAS Free

Performance Characteristics

| | |
|--------------------------------------------------|-------------------------------|
| Abrasion Resistance ASTM D4157 | 100,000 Double Rubs |
| Pilling ASTM D3511 (Brush Test) | Class 5 |
| Seam Slippage ASTM D4034 (Grab Test) | Warp: 94 lbs / Weft: 83.5 lbs |
| Break Strength ASTM D5034 | Warp: 249 lbs / Weft: 79 lbs |
| Wet Crocking AATCC 8 | Grade: 5 |
| Dry Crocking AATCC 8 | Grade: 5 |
| Colorfastness to Light AATCC 16 (Hours/Grade) | Hours: 40 / Grade: 4.5 |

Flammability

- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260