



Specifications

ACT® Registered Certification Marks



| | |
|------------------|-------------------------------------|
| Application | Upholstery, Indoor |
| Content | 100% PVC Vinyl |
| Backing | Brushed Polyester Knit |
| Finish / Topcoat | Resilience TX Soil/Stain Protection |
| Weight | 30.0 oz./yd. |
| Width | 54.000" |
| Fabric Shown | Up the Roll |
| Origin | Taiwan |
| Collection | Checkmate |

Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant

Performance Characteristics

| | |
|--|---------------------------------|
| Abrasion Resistance ASTM D4157 | 250,000 Double Rubs |
| Break Strength ASTM D751-06 | Warp: 98 lbs / Weft: 81 lbs |
| Tear Strength, Tongue Tear ASTM D751-06 | Warp: 6.9 lbs / Weft: 10.6 lbs |
| Tear Strength, Tack/Trap Tear ASTM D751-06 | Warp: 58.5 lbs / Weft: 46.2 lbs |
| Wet Crocking AATCC 8 | Grade: 5 |
| Dry Crocking AATCC 8 | Grade: 5 |
| Colorfastness to Light AATCC 16 (Hours/Grade) | Hours: 200 / Grade: 4 |
| Adhesion of Coating ASTM D751 | Warp: 8.2 lbs / Weft: 6.6 lbs |
| Cold Crack -20 Degrees | |

Flammability

- FMVSS 302
- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260