



Specifications

ACT® Registered Certification Marks	    
Application	Upholstery, Indoor/Outdoor
Content	100% Sunbrella Acrylic
Finish / Topcoat	Sunbrella Water & Stain Repellent
Weight	22.2 oz./yd.
Width	54.000"
Fabric Shown	Railroaded
Origin	USA
Repeat Horizontal	27.140"
Repeat Vertical	14.000"
Collection	Fusion

Product Notes

- Special Order Item

Performance Characteristics

Abrasion Resistance ASTM D4157	97,500 Double Rubs
Pilling ASTM D3511	Class 4.5
Seam Slippage ASTM D4034	Warp: 54.5 lbs / Weft: 98.1 lbs
Break Strength ASTM D5034	Warp: 378.3 lbs / Weft: 418.3 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 2,200 / Grade: 4

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013

Environment/Certifications

- California AB-2998 Compliant
- PFAS Free



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM