



Specifications

Table with 2 columns: Specification, Value. Rows include Application (Upholstery, Indoor), Content (100% PVC Vinyl), Backing (100% Polyester), Finish / Topcoat (Soil & Stain Resistant Topcoat), Weight (30.0 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), and Origin (Taiwan).

Product Attributes

- Sulfide Stain Resistant

Product Notes

- Inventory in Transition to California AB-2998 Compliance

Performance Characteristics

Table with 2 columns: Performance Characteristic, Value. Rows include Abrasion Resistance (250,000 Double Rubs), Break Strength (Warp: 121 lbs / Weft: 125 lbs), Tear Strength, Tongue Tear (Warp: 9.8 lbs / Weft: 11.7 lbs), Tear Strength, Tack/Trap Tear (Warp: 44.8 lbs / Weft: 53.7 lbs), Wet Crocking (Grade: 5), Dry Crocking (Grade: 5), Colorfastness to Light (Hours: 200 / Grade: 4), Adhesion of Coating (Warp: 4.3 lbs / Weft: 4.6 lbs), and Cold Crack (20 F).

Flammability

- FMVSS 302, UFAC Class 1, CA Technical Bulletin 117-2013, NFPA 260

Environment/Certifications

- PFAS Free, Formaldehyde Free, Phthalate Free, Prop 65 Compliant, REACH Compliant, RoHS Compliant