



Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl
Backing	75% Polyester, 25% Cotton
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	33.6 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan

Product Attributes

- Sulfide Stain Resistant

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 Double Rubs
Break Strength ASTM D751-06	Warp: 67 lbs / Weft: 78 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 7.1 lbs / Weft: 6.3 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 67 lbs / Weft: 64 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 11 lbs / Weft: 9.7 lbs
Cold Crack CFFA 10	- 20 F

Flammability

- FMVSS 302
- CA Technical Bulletin 117-2013
- UFAC Class 1
- NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- Formaldehyde Free
- REACH Compliant
- Prop 65 Compliant
- PFAS Free
- Phthalate Free
- RoHS Compliant



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM