



Specifications

Table with 2 columns: Specification, Value. Rows include ACT® Registered Certification Marks, Application (Upholstery, Indoor), Content (100% PVC Vinyl), Backing (75% Polyester, 25% Cotton), Finish / Topcoat (Soil & Stain Resistant Topcoat), Weight (33.6 oz./yd.), Width (54.000"), Fabric Shown (Up the Roll), and Origin (Taiwan).

Product Attributes

- Sulfide Stain Resistant

Performance Characteristics

Table with 2 columns: Performance Characteristic, Value. Rows include Abrasion Resistance (100,000 Double Rubs), Break Strength (Warp: 67 lbs / Weft: 78 lbs), Tear Strength, Tongue Tear (Warp: 7.1 lbs / Weft: 6.3 lbs), Tear Strength, Tack/Trap Tear (Warp: 67 lbs / Weft: 64 lbs), Wet Crocking (Grade: 5), Dry Crocking (Grade: 5), Colorfastness to Light (Hours: 200 / Grade: 4), Adhesion of Coating (Warp: 11 lbs / Weft: 9.7 lbs), and Cold Crack (- 20 F).

Flammability

- FMVSS 302, UFAC Class 1, CA Technical Bulletin 117-2013, NFPA 260

Environment/Certifications

- California AB-2998 Compliant, PFAS Free, Formaldehyde Free, Phthalate Free, REACH Compliant, Prop 65 Compliant, RoHS Compliant



