



UNITED FABRICS  
EXCLUSIVE



STAIN  
RESISTANT

PERMANENT SOIL & STAIN

### Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	53% Acrylic 40% Polyester 7% Viscose
Backing	None
Finish / Topcoat	Permanent Soil/Stain Protection
Weight	16.1 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Turkey
Collection	Cityscape

### Product Notes

- Prop 65 Compliant
- California AB-2998 Compliant
- PFAS Free

### Performance Characteristics

Abrasion Resistance ASTM D4157	50,000 Double Rubs
Pilling ASTM D3511 (Brush Test)	Class 5
Seam Slippage ASTM D4034 (Grab Test)	Warp: 78.1 lbs / Weft: 96.7 lbs
Break Strength ASTM D5034	Warp: 345.2 lbs / Weft: 123.1 lbs
Wet Crocking AATCC 8	Grade: 4.5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 40 / Grade: 4

### Flammability

- CA Technical Bulletin 117-2013
- NFPA 260