



Specifications

ACT® Registered Certification Marks



|                   |                                                |
|-------------------|------------------------------------------------|
| Application       | Upholstery, Indoor/Outdoor                     |
| Content           | 65.100% Sunbrella Acrylic<br>34.900% Polyester |
| Finish / Topcoat  | Sunbrella Water & Stain Repellent              |
| Weight            | 10.1 oz./yd.                                   |
| Width             | 54.000"                                        |
| Fabric Shown      | Railroaded                                     |
| Origin            | USA                                            |
| Repeat Horizontal | 8.890"                                         |

Performance Characteristics

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| Abrasion Resistance<br>ASTM D4157       | 57,500 Double Rubs              |
| Pilling<br>ASTM D3511 (Brush Test)      | Class 5                         |
| Seam Slippage<br>ASTM D4034 (Grab Test) | Warp: 34.3 lbs / Weft: 35.2 lbs |
| Break Strength<br>ASTM D5034            | Warp: 335.4 lbs / Weft: 318 lbs |
| Wet Crocking<br>AATCC 8                 | Grade: 5                        |
| Dry Crocking<br>AATCC 8                 | Grade: 5                        |
| Colorfastness to Light<br>AATCC 16      | Hours: 2,200 / Class: 4         |

Flammability

- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- PFAS Free
- Greenguard Gold Certified



(800) 347-8344

UNITEDFABRICS.COM

SALES@UNITEDFABRICS.COM