



Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl W/ Urethane Topcoat
Backing	Polyester Knit
Finish / Topcoat	PBG+ Vinyl Protection
Weight	30.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Costa Rica
Repeat Horizontal	18.000"
Repeat Vertical	18.000"
Collection	Checkmate

Product Notes

- Prop 65 Compliant
- Inventory in Transition to California AB-2998 Compliance

Performance Characteristics

Abrasion Resistance ASTM D4157	100,000 Double Rubs
Tensile Strength (Use Break Str. First) CFFA 17	Warp: 121 lbs / Weft: 72 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 5.6 lbs / Weft: 5.9 lbs
Wet Crocking AATCC 8	Grade: 4
Dry Crocking AATCC 8	Grade: 4
Colorfastness to Light CFFA 2 (Hours/Grade)	Hours: 1,000 / Class: 4
Adhesion of Coating ASTM D751	Warp: 3 lbs / Weft: 3 lbs
Cold Crack CFFA 10	- 10 F

Flammability

- UFAC Class 1
- NFPA 260
- CA Technical Bulletin 117-2013