



Specifications

ACT® Registered Certification Marks



|                  |                                |
|------------------|--------------------------------|
| Application      | Upholstery, Indoor             |
| Content          | 100% PVC Vinyl                 |
| Backing          | 100% Polyester                 |
| Finish / Topcoat | Soil & Stain Resistant Topcoat |
| Weight           | 5.7 oz./yd.                    |
| Width            | 54.000"                        |
| Fabric Shown     | Up the Roll                    |
| Origin           | Colombia                       |
| Collection       | <a href="#">Comfort Vinyls</a> |

Product Attributes

- Anti-Static
- Sulfide Stain Resistant

Performance Characteristics

|                                                  |                               |
|--------------------------------------------------|-------------------------------|
| Abrasion Resistance<br>ASTM D4157                | 100,000 Double Rubs           |
| Flex Resistance<br>ASTM D2097                    | 30,000 Cycles                 |
| Tear Strength, Tongue Tear<br>ASTM D2261         | Warp: 5.6 lbs / Weft: 5.9 lbs |
| Wet Crocking<br>AATCC 8                          | Grade: 4                      |
| Dry Crocking<br>AATCC 8                          | Grade: 4                      |
| Colorfastness to Light<br>AATCC 16 (Hours/Grade) | Hours: 1,000 / Grade: 4       |
| Adhesion of Coating<br>ASTM D751                 | Warp: 3.3 lbs / Weft: 3.3 lbs |
| Cold Crack<br>CFFA 10                            | - 10 F                        |

Flammability

- UFAC Class 1
- CA Technical Bulletin 117-2013
- NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- PFAS Free
- Phthalate Free