




Specifications

ACT® Registered Certification Marks



Application	Upholstery, Indoor
Content	100% PVC Vinyl
Backing	100% Polyester
Finish / Topcoat	Soil & Stain Resistant Topcoat
Weight	30.0 oz./yd.
Width	54.000"
Fabric Shown	Up the Roll
Origin	Taiwan
Collection	220: Faux Leather Studio 225: Faux Leather Studio: Leather Looks 219: Trail Mix

Product Attributes

- Sulfide Stain Resistant

Performance Characteristics

Abrasion Resistance ASTM D4157	250,000 Double Rubs
Break Strength ASTM D751-06	Warp: 105 lbs / Weft: 92 lbs
Tear Strength, Tongue Tear ASTM D751-06	Warp: 6.4 lbs / Weft: 7.5 lbs
Tear Strength, Tack/Trap Tear ASTM D751-06	Warp: 54.3 lbs / Weft: 42.9 lbs
Wet Crocking AATCC 8	Grade: 5
Dry Crocking AATCC 8	Grade: 5
Colorfastness to Light AATCC 16 (Hours/Grade)	Hours: 200 / Grade: 4
Adhesion of Coating ASTM D751	Warp: 6.3 lbs / Weft: 6.3 lbs
Cold Crack CFFA 10	- 20 F

Flammability

- FMVSS 302
- CA Technical Bulletin 117-2013
- UFAC Class 1
- NFPA 260

Environment/Certifications

- California AB-2998 Compliant
- Phthalate Free
- REACH Compliant
- PFAS Free
- Prop 65 Compliant
- RoHS Compliant